

550, 650

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number
WO 2004/085887 A1

(51) International Patent Classification⁷: F16H 61/30, 61/28

(21) International Application Number: PCT/GB2004/001240

(22) International Filing Date: 24 March 2004 (24.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 0307118.0 27 March 2003 (27.03.2003) GB

(71) Applicant (for all designated States except US): RICARDO UK LIMITED [GB/GB]; Bridge Works, Shoreham-by-Sea, West Sussex BN43 5FG (GB).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BARNES, Robert, John [GB/GB]; 15 St George Drive, Rawnsley, Hedgesford, Cannock, Staffordshire, WS12 0FB (GB).


(74) Agents: HIBBERT, Juliet et al.; Kilburn & Strode, 20 Red Lion Street, London WC1R 4PJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: TRANSMISSION ACTUATOR AND CONTROL METHOD THEREFOR



WO 2004/085887 A1

(57) Abstract: An actuator for actuating a gear shift mechanism in a vehicular transmission system, the actuator comprising: an actuator body (40) having an opening (43) for the transport of fluid into and out of the actuator body; an actuating member (42) within the actuator body, moveable by the fluid; and a control device (410, 416) operable to control independently the pressure of the fluid and the flow of the fluid.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*